In the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

 (Previously Presented) A method of deploying filters for use in processing audio signals, comprising:

calculating a filter for each of a plurality of frequency bands;

determining a distance between coefficients of filters in adjacent frequency bands;

and

merging filters with a shortest distance between coefficients to produce a set of final filters:

determining whether a stronger signal is mixed with one or more weaker signals in frequency bands covered by the final filters; and

recalculating ones of the final filters determined to have a stronger signal mixed with one or more weaker signals in a corresponding frequency band, the ones of the final filters being recalculated for the respective stronger signal.

- 2. (Original) The method of claim 1, wherein said filters are TNS filters.
- (Original) The method of claim 1, wherein said coefficients are PARCOR coefficients.
- (Previously Presented) The method of claim 1, wherein said merging involves
 calculating a new filter for a frequency range comprising said adjacent frequency bands of
 said filters with said shortest distance.

(Previously Presented) A method of deploying filters for use in processing audio signals, comprising:

calculating a filter for each of a plurality of frequency bands;

comparing coefficients of filters in adjacent frequency bands to identify a pair of filters with a shortest Euclidean distance between coefficients:

merging said pair of filters to produce a set of final filters;

repeating all previously recited acts until a predetermined number of total filters is reached;

determining whether a stronger signal is mixed with one or more weaker signals in frequency bands covered by the final filters; and

recalculating ones of the final filters determined to have a stronger signal mixed with one or more weaker signals in a corresponding frequency band, the ones of the final filters being recalculated for the respective stronger signal.

- (Original) The method of claim 5, wherein said coefficients are PARCOR coefficients.
- (Previously Presented) The method of claim 5, wherein said merging involves
 calculating a new filter for a frequency band comprising said adjacent frequency bands of
 said filters with said shortest Euclidean distance.
- (Previously Presented) The method of claim 5, further comprising: using at least one of said recalculated ones of the filters for an entire extent of said frequency range.

 (Original) The method of claim 8, wherein said strongest signal is identified based on energy/bin within said frequency range.

10-17. (Canceled)